

Super Lube®

El penetrante Sintético Super Lube® es un aceite sintético solvente que actúa rápidamente atacando al óxido y la corrosión. El producto se infiltra en lugares de difícil alcance permitiendo así el aflojamiento de pernos, tuercas y tornillos corroídos y oxidados. Penetra, lubrica y deja una capa protectora que previene contra el óxido y la corrosión.

DIRECCIONES: Agite bien antes de usar. Use el tubo rígido o cánula para una aplicación de punto preciso.

APLICACIONES:

- Limpia
- Penetra
- Afloja partes oxidadas
- Afloja mecanismos pegajosos
- Pone fin al chirrido
- Protege contra el óxido y la corrosión
- Dispersa la humedad
- Deja una capa lubricante protectora

PRECAUCIONES: CONTIENE DESTILADOS DE PETRÓLEO. No rocíe cerca del calor, chispas o flama abierta. No aguiere o incliniere el envase. Temperatura alta puede ocasionar que el envase estalle. No exponga a alta temperatura o almaceene a mas de 49°C (120°F). Evite inhalación de los vapores o la rociada del pulverizador. Evite el contacto con la piel y ojos. En caso del contacto con los ojos enjuague con abundante agua.

Puede ser fatal si se ingiere. Si se ingiere no induzca el vómito. Consulte al médico. Use en lugares bien ventilados.

MANTENGA FUERA DEL ALCANCE DE LOS NIÑOS.

LA138 - Syncopen Synthetic Penetrant-Proof 31dps5
Black

SYNCOPEN® SYNTHETIC PENETRANT

PENETRANTE SINTÉTICO

**DANGER: FLAMMABLE
CONTENTS UNDER PRESSURE
HARMFUL OR FATAL IF SWALLOWED
SEE SIDE PANEL**

**PELIGRO: INFLAMABLE
CONTENIDO BAJO PRESIÓN PELIGROSO O
FATAL
SI SE INGIERE. LEA LAS PRECAUCIONES
AL REVERSO**

NET WT. 11 oz. / CONT. NETO 311g

3/9/2011, 11:11 AM

Super Lube® Synthetic Penetrant is a super fast-acting penetrating solvent and synthetic oil that cuts through rust or corrosion and travels into hard to reach areas to allow easy removal of rusted and corroded screws, nuts or bolts. Penetrates, lubricates and leaves a protective film to help prevent future rusting or corrosion.

DIRECTIONS: Shake well before using. Use handy extension tube for pinpoint application.

APPLICATIONS:

- Cleans
- Penetrates
- Loosens rusted parts
- Frees sticky mechanisms
- Stops squeaks
- Protects against rust & corrosion
- Drives out moisture
- Leaves a protective lubricating film

WARNINGS: CONTAINS PETROLEUM DISTILLATES.

Keep away from heat, sparks and open flame. Do not puncture or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperatures above 120°F (49°C). Avoid breathing of vapor or spray mist. Avoid contact with skin or eyes. If accidentally sprayed in eyes, wash and flush thoroughly with water. May be fatal if swallowed. If swallowed, do not induce vomiting. Call physician.

Use with adequate ventilation.

KEEP OUT OF REACH OF CHILDREN.

USDA Rated H-1

Super Lube® and **Syncopen®** are registered trademarks of Synco Chemical Corporation

Made in U.S.A. by **SYNCO CHEMICAL CORPORATION**, Bohemia, NY 11716

www.super-lube.com

Consumer Info Line: 800-253-LUBE



LA138



LA138 - Syncoopen Synthetic Penetrant+Proof 3d.p65
PANTONE 116 CVC

3/9/2011, 11:11 AM



LA138 - Syncoopen Synthetic Penetrant+Proof 3d.p65
PANTONE 172 CVC

3/9/2011, 11:11 AM

LA138 - Syncoopen Synthetic Penetrant+Proof 3d.p65
PANTONE 293 CVC

3/9/2011, 11:11 AM






LA138 - Syncoopen Synthetic Penetrant+Proof 3d.p65
PANTONE 368 CVC

3/9/2011, 11:11 AM

Super Lube



SYNCOPEN




North Carolina
Program Listed H-1
Registration #138740



PANTONE 877 CVC